

Recessed Lights



LED Recessed Lighting



4" Snap-In Recessed LED Downlight
410D20490

- 650-690 lms
- 93° beam angle
- 10.5 W
- >90 CRI
- High color rendering index renders colors bright and true
- Built in driver for superior dimmability
- 50,000 hour lifespan
- White Finish
- Rated for wet locations, air tight, and IC (insulation contact)
- Springs clips for easy installation



6" Snap-in Recessed LED Downlight
410D21690

- 1050-1150 lms
- 95.6° beam angle
- 15 W
- >90 CRI
- High color rendering index render color bright and true
- Built in driver for superior dimmability
- 50,000 hour lifespan
- White finish
- Rated for wet locations, air tight, and IC (insulation contact)
- Spring clip for easy installation

LED Recessed Can Lighting



SUNSET DIMMING LED DOWNLIGHT
DLR56-SD-1007-WH-BF 6" SUNSET



5" & 6" LED DOWNLIGHT
DLR56-2709-120V-4K-WH

- Cast aluminum housing with white polymer trim
- Polystyrene diffuser and reflector cone create a uniform light distribution that reduces glare without sacrificing lumen output
- Utilizes high performing LEDs with greater than 90 CRI and an R9 greater than 60
- Dimmable to 10% with most TRIAC dimmers
- Dims smoothly from 3000K to 2000K
- Thermally protected, high efficiency driver
- Operating temperature rating of 0°F to 120°F (-18°C to 49°C) Input voltage of 120V
- Lifetime rated for greater than 60,000 hours
- LM-79, LM-80 testing performed in accordance with IESNA standards.
- Available in White polymer baffled trim
- >90 CRI
- Compatible with most 5" and 6" recessed housings
- >60,000 hour life expectancy
- Easy installation with adjustable torsion springs
- Integrated Trim available in 4 colors
- Dimmable to 10% with most dimmers
- Durable construction
- 5 year warranty
- Edison Base (GU24 socket adaptors available)
- Suitable for use in IC Rated recessed housings
- Wet location rated - perfect for shower applications

LED Recessed Can Lighting



5" & 6" DOWNLIGHT GIMBAL
DLG56-10-120-4K-WH



4" SUNSET DIMMING LED DOWNLIGHT
DLR4-SD 1005-WH-BF

- Durable stamped steel construction with die cast aluminum heat sink
 - Polycarbonate diffuser and reflector cone create a uniform light distribution that reduces glare
 - Greater than 90 CRI and an R9 greater than 50
 - Dimmable to 10% with most standard dimmers
 - Thermally protected, high efficiency driver standard
 - Operating temperature rating of 0°F to 120°F (-18°C - 49°C)
 - LM-79, LM-80 testing performed in accordance with IESNA standards
- Cast aluminum housing with white polymer trim
 - Polystyrene diffuser and reflector cone create a uniform light distribution that reduces glare without sacrificing lumen output
 - Utilizes high performing LEDs with greater than 90 CRI and an R9 greater than
 - Dimmable to 10% with most TRIAC dimmers
 - Dims smoothly from 3000K to 2000K
 - Thermally protected, high efficiency driver
 - Operating temperature rating of 0°F to 120°F (-18°C to 49°C)
 - Input voltage of 120V
 - Lifetime rated for greater than 60,000 hours
 - LM-79, LM-80 testing performed in accordance with IESNA standards.
 - Available in White polymer baffled trim

Recessed Can Lighting



5" SHALLOW CONE BAFFLE TRIM
15512WH

This five-inch trim uses a white baffle cone and is best used in spaces where you are looking to direct light downward, to reduce glare and to absorb excess light. Suitable for IC rated housings.

